



Shell *Coolant Essential Ready to Use*

MEG based pre-diluted coolant / antifreeze

Provides the protection* that the cooling system components need under elevated and low temperatures (down to -37°C).

* Always follow instructions from your equipment/vehicle manufacturer.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- Ready to use Coolant that has anti rust & anti corrosion additives, low freezing point. Provides effective heat transfer at high engine operating temperatures.

Specifications, Approvals & Recommendations

- Meets ASTM D1384 as required in ASTM D3306
For a full listing of equipment approvals and recommendations, please consult your local representative.

Typical Physical Characteristics

Properties		Method	Shell Coolant Essential Ready to Use
Colour		Visual	Green
Freeze Point	As sold °C	ASTM D1177	-37
pH	As sold	ASTM D1287	7.9
Reserve Alkalinity	As sold mL 0.1N HCl	ASTM D1121	8.5
Specific Gravity	@15.6°C (60°F)	ASTM D1122	1.065

These characteristics are typical of current production.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used coolant. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

• Protect the Environment

Take used coolant to an authorised collection point. Do not discharge into drains, soil or water.