



Shell Super Plus Motor Oil 20W-50

Shell Super Plus Motor Oil 20W-50 is designed to help provide consistent engine performance.



It works hard to help protect against engine sludge and reduce wear

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- Formulated using high-quality base oils and additives, the new Shell Super Plus Motor Oil 20W-50 (API SN) has a more advanced engine oil formulation.
- It offers improved performance, better engine protection
 - 50% reduction in harmful piston deposits*
 - 45% greater oxidation control - improved resistance to chemical breakdown*
 - 25% better wear protection*

*Compared with API SL specification

Main Applications

- Shell Super Plus Motor Oil 20W-50 is suitable for a wide variety of vehicles for everyday driving condition. Suitable for gasoline, gas or ethanol containing fuels.

Specifications, Approvals & Recommendations

- API SN

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks

Typical Physical Characteristics

Properties			Method	Shell Super Plus Motor Oil 20W-50
Kinematic Viscosity	@100°C	cSt	ASTM D445	17.67
Kinematic Viscosity	@40°C	cSt	ASTM D445	159.4
Viscosity Index			ASTM D2270	122
MRV	@-20°C	cP	ASTM D4684	19 200
Density	@15°C	kg/m ³	ASTM D4052	879.5
Flash Point			ASTM D92	252
Pour Point			ASTM D97	-30

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

Health and Safety

Shell Super Plus Motor Oil 20W-50 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.